



EZG[®]

Manufacturing

EZG Mixers[®]

Model EZG7

- 1/2 to 2 bag capacity or 7 cu. ft. (.2 m³)
- 7.9 HP Honda[®] Gas Engine (Standard)
- Will mix up to 3/4" (1.9 cm) aggregate
- Discharges up to 21" high without the use of blocking
- 48" load height
- Manual recoil start
- 3/16" drum thickness
- Empty weight 820 lb. (371.9 kg)
- 4" x 6" rectangular structural tubing
- 1 1/4" solid steel shaft
- 2" ball hitch
- Pintle hitch available
- Optional leg kit
- Electric models available



Model EZG7

Model EZG9

- 2 1/2 to 3 bag capacity or 9 cu. ft. (.25 m³)
- 7.9 HP Honda[®] Gas Engine (Standard)
- Will mix up to 3/4" (1.9 cm) aggregate
- Discharges up to 20" high without the use of blocking
- 56" load height
- Manual recoil start
- 3/16" drum thickness
- Empty weight 970 lb. (440 kg)
- 4" x 6" rectangular structural tubing
- 1 3/4" solid steel shaft
- 2" ball hitch
- Optional leg kit
- Pintle hitch available
- Electric models available



Model EZG9

Who We Are

For close to 20 years, we have honed our precision metal fabrication services. With roots in the contracting industry, CEO Damian Lang started the EZ Grout equipment line to improve the efficiency on his own masonry job sites. Since then, EZG Manufacturing has expanded to include precast, refractory, cleaning, and fencing equipment along with it's award winning EZ Grout equipment line. We also have our custom fabrication and design shop to meet all of your unique needs.

Model EZG12

- 3 to 4 bag capacity or 12 cu. ft. (.34 m³)
- 11.7 HP Honda® Gas Engine (Standard)
- Will mix up to 3/4" (1.9 cm) aggregate
- Discharges up to 20" high without the use of blocking
- 56" load height
- Manual recoil start
- 1/4" drum thickness
- 4" x 7" rectangular structural tubing
- 1 3/4" solid steel shaft
- 2" ball hitch
- Pintle hitch available
- Electric models available



Model EZG12

Rob Roussel, Robert's Masonry

"Being a smaller Mason contractor we needed a mixer we could count on. Yes, there were cheaper mixers on the market but we needed a mixer that would stay out in the field and out of the shop. We have been using both EZG's manual and hydraulic mixers for over 4 years and plan on adding more to our fleet when needed. Their uphill grout hog is amazing. We watch our competition who are still in the stone age using buckets and tubs to grout and are so happy we have EZG's Grout Hog. The customer service at EZG is also fantastic."

Model	EZG7	EZG9	EZG12
Capacity - cu. ft (m ³)	7 (.2)	9 (.25)	12 (.34)
Capacity - Bags	1 1/2 to 2	2 to 3	3 to 4
Power Source* HP (kw)	Honda GX240 7.9 (5.6)	Honda GX240 7.9 (5.6)	Honda GX390 11.7 (8.7)
Engine Starting	Manual Recoil	Manual Recoil	Manual Recoil
Electric Motor - 1PH/115V HP	1.5	N/A	N/A
Electric Motor - 1PH/230V HP	N/A	5	10
Electric Motor - 3PH/230V HP	N/A	5	10
Electric Motor - 3PH/460V HP	N/A	5	10
Drum Thickness in.	3/16	3/16	1/4
Forklift Pockets	Standard	Standard	Standard
Discharge Height in. (cm)	22 (56)	20 (51)	20 (51)
Load Height in. (cm)	49 (124)	56 (142)	56 (142)
Dump Action	Manual	Manual	Manual
Drive System	Chain	Chain	Chain
Dimensions L x W x H in. (cm)	73 x 47 x 58 (185 x 119 x 147) 104 L w/tongue (264) 70 H w/dump handle (178)	71 x 47 x 62 (180 x 119 x 157) 107 L w/tongue (272) 77 H w/dump handle (196)	73 x 47 x 67 (185 x 119 x 170) 110 L w/tongue 77 H w/dump handle (279)
Weight lb. (kg)	850 (386)	970 (440)	1150 (522)



1-800-417-9272 | ezgmfg.com
1833 North Riverview Road
Malta, OH | 43758

