

# Hog Pump® Mixer Combo

## Durable, Efficient, Uniform Mixing and Delivery.


The EZG Hog Pump Mixer Combo Unit (Model HPMC-220) is a powerhouse designed for high-density mixing and high pressure pumping. Its robust design and high-torque pan mixer, combined with a high-pressure piston pump, make it the go-to solution for dense refractory shotcrete and pumping cast applications across a wide range of industries.

From steel mills and cement plants to glass manufacturing, power generation, and petrochemical facilities, this versatile machine handles the most demanding refractory installations with ease. It excels in pumping refractory materials vertically over 300 feet (91 meters) and is equally adept at shotcreting applications.

- Powerful JD 250HP T4F engine for reliable performance
- Robust 8 paddle carosel pan mixer ensures thorough material mixing
- High-pressure piston pump delivers consistent and efficient pumping
- Hydraulic front jack and 4 manual outrigger jacks ensure stability on the jobsite
- Convenient on-board integrated power washer
- Optional corded pendant for added convenience during operation



Ultra high-pressure piston pump consistently delivers 18 yards per hour



Bag break sits atop a 4000 lb. / 2 yd. pan mixer designed to handle dense refractory shotcrete



EZG's patented paddle design with 8 blades ensures uniform clog-free mixing in the remix hopper.

SPECIFICATIONS	HPMC-220
Pump:	4.5" x 30" material tube (100 m x 910 mm)
Pump Pressure:	2,200 psi (152 bar)
Output:	0-18 yard/hr
Discharge:	4" (100 mm)
Variable Speed Pan Mixer:	0-39 RPM / 8 paddle 4,000 lb. capacity (1,800 kg)
Variable Speed Remix Hopper:	0-25 RPM / 8 paddle 4000 lb. capacity (1,800 kg)
Engine:	JD 250HP T4F
Fuel Cell:	100 gal. (378 L)
Water Tank:	20 gal. (75 L)
Weight:	21,000 lb. (9,525 kg)



1-800-417-9272 / [ezgmfg.com](http://ezgmfg.com) / [sales@ezgmfg.com](mailto:sales@ezgmfg.com)  
1833 N. Riverview Road, Malta, Ohio 43758

EZG Manufacturing is a division of EZ Grout Corporation. All EZG Manufacturing products are backed by our **two-year warranty** on parts unless otherwise stated and are now available for order.

