## **EFPC Series**

**EZG Forward Vibratory Plate Compactors** distinguish themselves with premium operating comfort, compact dimensions and optimum running characteristics. The EFPC is ideal for landscape and hardscape applications including: asphalt, gravel, sand, brick, pavers and more.

- Anti-vibration handle reduces hand/arm fatigue and folds for simple transport and storage
- Offered in three different plate sizes
- Large capacity water tank for asphalt applications and multi-stage filtration system
  Wrap around engine protection doubles as secure lifting point
- Optional polyurethane pad to protect material from scratches and white capping









Reliable, easy to<br/>access pull startIntegrated wheel kit<br/>drops and locks for<br/>easy transport of<br/>gasoline engine.Reliable, easy to<br/>drops and locks for<br/>easy transport of<br/>equipment.



Simple installation and removal of optional polyurethane pads

MODEL	EFPC60W	EFPC70W	EFPC90C
Dimensions LxWxH in. (mm)	<b>38" x 14" x 41"</b> (970 x 360 x 1050)	<b>48" x 40" x 50"</b> (970 x 360 x 1050)	<b>43" x 19" x 39"</b> (1100 x 500 x 993)
Plate Size in. (mm)	20" x 14.2" (510 x 360)	20.5" x 17.7" (520 x 450)	23.2" x 19.7" (590 x 500)
Power Source	Honda® GX160 4.8 HP (3.6kw)	Honda® GX160 4.8 HP (3.6kw)	Honda <sup>®</sup> GX160 4.8 HP (3.6kw)
Centrifugal Force / Vibration Frequency	2,358 lbs. (1,070 kgf) 5,460 v.p.m.	2,778 lbs. (1,260 kgf) 5,640 v.p.m.	3,461 lbs. (1,570 kgf) 5,640v.p.m.
Tank Capacity gal. (L)	1.6 gal (6 L)	3.7 gal (12 L)	3.7 gal (12 L)
Operating Weight	148 lbs. (67 kg)	163 lbs. (74 kg)	209 lbs. (95 kg)



## **1-800-417-9272 / ezgmfg.com / sales@ezgmfg.com** 1833 N. Riverview Road, Malta, Ohio 43758

EZG Manufacturing is a division of EZ Grout Corporation. All EZG Manufacturing products are backed by our **two-year warranty** on parts unless otherwise stated and are now available for order.

