


EZG® Outrigger Pads

The Ultimate Choice for Unparalleled Reliability.

Empowering your teams and equipment with unwavering strength, impeccable load distribution, and ergonomic safety. Our meticulously crafted outrigger pads are expertly designed, utilizing a specially engineered thermoplastic that withstands immense pressure. Resistant to water and chemicals, these pads are available in four sizes, catering to diverse equipment stabilization requirements. Embrace the assurance of working securely, seamlessly, and economically in the most challenging environments.

- Sturdy ergonomic design with durable handles for easy 1-2 person carry or roll
- Safety texture and radius edges and corners
- Extraordinary power, stability, and longevity facilitate effective distribution of substantial loads.
- Resistant to breakage or splitting caused by prolonged exposure to water, sun or extreme cold



SPECIFICATIONS	OP36	OP48	OP24-12	OP24-24
Dimensions: (L x W x H)	36" -round (914 mm)	48" -round (1219 mm)	24" x 12" x 2" (610 x 305 x 51 mm)	24" x 24" x 2" (610 x 610 x 51 mm)
Thickness	2 inch (51 mm)	2 inch (51 mm)	2 inch (51 mm)	2 inch (51 mm)
Approx Area	5.24 sq.ft. (0.49m ²)	10.06 sq.ft. (0.94 m ²)	1.58 sq.ft. (0.15 m ²)	3.16 sq.ft. (0.34 m ²)
Compressive Strength*	500 psi	500 psi	500 psi	500 psi
Working Load*	95,000 lbs. (43,091 kg)	120,000 lbs. (54,431 kg)	28,500 lbs. (12,700 kg)	57,000 lbs. (25,855 kg)
Weight	70 lbs. (32 kg)	120 lbs. (54 kg)	20 lbs. (9 kg)	40 lbs. (18 kg)

* maximum allowable pressure / load limit based on application



1-800-417-9272 / ezgmfg.com / sales@ezgmfg.com
1833 N. Riverview Road, Malta, Ohio 43758

EZG Manufacturing is a division of EZ Grout Corporation. All EZG Manufacturing products are backed by our **two-year warranty** on parts unless otherwise stated and are now available for order.

