

Mud Hog®

Maximize Efficiency and Durability on Your Job Site.

The Mud Hog series is engineered for jobsite durability and ease of operation, designed to handle mortar, grout, and concrete. These mixers are low-loading and high-dumping to minimize labor fatigue, featuring patented vertical paddles with reversible rubber blades to reduce splashing and prevent clogging. Known for their quality, performance, and safety, Mud Hog mixers are the premier standard in the industry, distributed internationally.

Available globally, these mixers offer a range of capabilities and options designed to make your job easier and more efficient.

Universal Features:

- Mixes up to 3/4" aggregate
- Hydraulic drive and hydraulic dump
- Reversible mixing paddles with a one-year warranty on rubber blades
- Adjustable height for ease of loading and dumping
- Fork pockets accessible from all four sides (on applicable models)
- Comes standard with electric start Honda® engine— diesel engine, or electric motor options available

Model MH9:

- 2 to 3 bag capacity* or 9 cu.ft.
- GX270 8.4 hp Honda® engine
- Tow package with highway tires & torsion axel
- Optional brake and light kit

Model MH12:

- 3 to 4 bag capacity* or 12 cu.ft.
- GX390 11.7 hp Honda® engine w/ electric start

Model MH20:

- 6 to 7 bag capacity* or 20 cu.ft.
- 5/16" thick steel rolled drum and 3/8" thick steel drum ends
- GX390 11.7 hp Honda® engine w/ electric start
- Tow package with highway tires & torsion axel
- Compacts to fit in standard 8 ft. truck bed



Optional solid grate cover, with two separate openings for adding mix and water, helps control dust on the job site.



Forward / reversible mixing with patented vertical paddles and rubber blades prevents clogging, ensuring an optimal quality mix.



Easy-to-access gaskets, and seals are just one of the many features that simplify upkeep and maintenance.



* Capacities estimated based on 80 lb. bags

Increase efficiency, profitability and safety on the job.

Mud Hog® Series Specifications

MODEL	MH9	MH12	MH20
Dimensions: (L x W x H)	81" x 35" x 54" (2057 x 889 x 1372 mm)	82" x 42" x 49" (2082 x 1067 x 1245 mm)	96" x 56" x 51" (2438 x 1422 x 1295 mm)
Adjustable Discharge Height	Up to 26" (660 mm)	Up to 49" (1245 mm)	Up to 51" (1295 mm)
Dump Action	Hydraulic	Hydraulic	Hydraulic
Capacity	9 cu.ft. (0.25 m³)	12 cu.ft. (0.34 m³)	20 cu.ft. (0.57 m³)
Capacity - Bags*	2 to 3	3 to 4	6 to 7
Max Aggregate Size	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)
Power Source	Honda GX270 8.4 hp (6.2 kw)	Honda GX390 11.7 hp (8.7 kw)	Honda GX390 11.7 hp (8.7 kw)
Engine Starting	Manual Recoil	Recoil/Electric	Recoil/Electric
Drive System	Hydraulic	Hydraulic	Hydraulic
Empty Weight	1400 lbs. (635 kg)	1677 lbs. (761 kg)	2278 lbs. (1033 kg)
Drum Thickness	1/4"	End 3/8"; Wrap 1/4"	End 3/8"; Wrap 5/16"
Forklift Pockets	Optional	Standard	Standard
Axle Kit	Standard	Optional	N/A

* Capacities estimated based on 80 lb. bags



MODEL	OPTION
MH9LIGHTKIT	Tail Light Kit, Model MH9
MHLIGHTKIT	Tail Light Kit, Model MH12
HMH-A-1	High Rise Conversion Kit, MH12



[VIDEO]



Love it? We want to hear from you.

Snap a photo or capture a video of your team putting any of our Mud Hogs to use and post it. Remember to tag us @EZG and use #leanmasonry, in your post.

... Thank you for your continued commitment to the EZG product line.



1-800-417-9272 / ezgmfg.com / sales@ezgmfg.com
1833 N. Riverview Road, Malta, Ohio 43758

EZG Manufacturing is a division of EZ Grout Corporation. All EZG Manufacturing products are backed by our **two-year warranty** on parts unless otherwise stated and are now available for order.

